

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
18 March 2004 (18.03.2004)


PCT

(10) International Publication Number  
**WO 2004/021903 A1**

- (51) International Patent Classification<sup>7</sup>: A61B 17/72 (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (21) International Application Number: PCT/EP2003/009677
- (22) International Filing Date: 1 September 2003 (01.09.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 02019637.4 3 September 2002 (03.09.2002) EP
- (71) Applicant and  
(72) Inventor: PENNIG, Dietmar [DE/DE]; Hans-Driesch  
Strasse 12, 50935 Koln (DE).
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- (74) Agents: BOTTI, Mario et al.; Botti & Ferrari S.r.l., Via Locatelli, 5, I-20124 Milano (IT).
- Published:  
— with international search report

[Continued on next page]

(54) Title: SYSTEM FOR FIXATION OF BONE FRACTURES



(57) **Abstract:** The present invention relates to a system (1) for improving the fixation of proximal fractures of the humerus, including at least a humeral nail (10) to be inserted in a humeral shaft (9) and comprising at least proximal transversal holes (5, 6, 7) for the passage of corresponding locking screws (3), at least a screw of said locking screws (3) having a screw head (4) and a screw body (31). The system further includes at least an intermediate plate element (15) inserted between the screw head (4) and the bone cortex surface (14) so that the head (4) is abutting against the plate (15). The intermediate plate element (15) is slightly bent to adhere substantially to the bone cortex surface (14) and comprises a couple of elongated arm portions (18, 19) that are inserted in an astride position on the screw body before the final fastening of the screw head (4). This solution allows to enlarge the abutting surface of the locking screw head against the bone cortex thus allowing a stronger fastening action and avoiding a rotation of the screw.

WO 2004/021903 A1

BEST AVAILABLE COPY

Express Mail Label  
EV315505119US